



## HOBO<sup>®</sup> MX1102 Data Logger

Carbon Dioxide - Temp - RH

Onset's HOBO MX1102 CO<sub>2</sub> logger makes it more convenient than ever to measure and record CO<sub>2</sub> in buildings and other non-condensing environments. It measures CO<sub>2</sub> from 0 – 5,000 parts per million (ppm) – and our free HOBOMobile app\* allows you to access data right from your mobile phone or tablet within a 100-foot range.

The MX1102 also features a USB port so it can be used with a computer running HOBOWare graphing and analysis software.




### Key Advantages:

- Wireless communication via Bluetooth Low Energy (BLE) Technology
- Six month battery life at 5-minute CO<sub>2</sub> logging rate
- Easy to deploy and offload using free HOBOMobile App
- Visual and audible high & low alarm thresholds
- Self-calibrating NDIR CO<sub>2</sub> sensor technology ensures optimal accuracy and lower maintenance costs
- Patented connectivity technology

## HOBO MX1102 Data Logger Specifications

Temperature Sensor	
Range	0° to 50°C (32° to 122°F)
Accuracy	±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)
Resolution	0.024°C at 25°C (0.04°F at 77°F)
Drift	<0.1°C (0.18°F) per year
RH Sensor	
Range	1% to 70% RH when CO <sub>2</sub> sensor is enabled (non-condensing) 1% to 90% RH when CO <sub>2</sub> sensor is disabled (non-condensing)
Accuracy	±2% from 20% to 80% typical to a maximum of ±4.5% including hysteresis at 25°C (77°F); below 20% and above 80% ±6% typical
Resolution	0.01%
Drift	<1% per year typical
CO <sub>2</sub> Sensor	
Range	0 to 5,000 ppm
Accuracy	±50 ppm ±5% of reading at 25°C (77°F), less than 70% RH and 1,013 mbar
Warm-up Time	15 seconds
Calibration	Auto or manual to 400 ppm
Non-linearity	<1% of FS
Pressure Dependence	0.13% of reading per mm Hg (corrected via user input for elevation/altitude)
Operating Pressure Range	950 to 1,050 mbar (use Altitude Compensation for outside of this range)
Compensated Pressure Range	-305 to 5,486 m (-1,000 to 18,000 ft)
Sensing Method	Non-dispersive infrared (NDIR) absorption
Response Time	
Temperature	12 minutes to 90% in airflow of 1 m/s (2.2 mph)
RH	1 minute to 90% in airflow of 1 m/s (2.2 mph)
CO <sub>2</sub>	1 minute to 90% in airflow of 1 m/s (2.2 mph)
Logger	
Radio Power	1 mW (0 dBm)
Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
Wireless Data Standard	Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)
Logger Operating Range	0° to 50°C (32° to 122°F); 0 to 95% RH (non-condensing)
Logging Rate	1 second to 18 hours
Logging Modes	Fixed interval (normal, statistics) or burst
Memory Modes	Wrap when full or stop when full
Start Modes	Immediate, push button, date & time, or next interval
Stop Modes	When memory full, push button, date & time, or after a set logging period
Time Accuracy	± 1 minute per month at 25°C (77°F)
Power Source	4 AA 1.5 Volt batteries (user replaceable) or USB power source (5 V DC, 2 Watts)

<b>Battery Life</b>	6 months, typical with logging and sampling intervals of 5 minutes or slower; 6 months or less with logging and sampling intervals faster than 5 minutes while logging CO <sub>2</sub> . Entering burst logging mode will impact battery life. With HOBOMobile use, battery life can be reduced by remaining connected, excessive readouts, checking of Full Status Details, audible alarms, and paging. Visual/audible alarms and other events can have a marginal impact on battery life.
<b>Memory</b>	128 KB (84,650 measurements, maximum)
<b>Download Type</b>	USB 2.0 interface or via Bluetooth Smart
<b>Full Memory Download Time</b>	20 seconds via USB; approximately 60 seconds via Bluetooth Smart, may take longer the further the device is from the logger
<b>LCD</b>	LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range
<b>Size</b>	7.62 x 12.95 x 4.78 cm (3.0 x 5.1 x 1.88 inches)
<b>Weight</b>	267.4 g (9.43 oz)
<b>Environmental Rating</b>	IP50
	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

## Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email [sales@onsetcomp.com](mailto:sales@onsetcomp.com)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support [www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation  
 470 MacArthur Boulevard  
 Bourne, MA 02532